



IAGSA Member Self-Assessment Questionnaire

Introduction: All IAGSA Active Members (survey companies) are required to complete and submit the Self-Assessment Questionnaire on an annual basis. IAGSA Associate Members such as air service providers, are not required to complete the questionnaire however, they may find it a useful reference as part of their internal audit process. The intent of this self-assessment process is to increase transparency of compliance levels within our membership through the publishing of completed assessments in the members-only area of our website, improve awareness of IAGSA Recommended Practices by requiring members to conduct an annual internal audit, and, in the case of non-conformances or variances, to drive our Notice of Difference process. This program does not replace the in-person audits conducted by IAGSA, but it does shift the focus to that of verification and surveillance.

Instructions: The questionnaire is derived from the Recommended Practices contained within the IAGSA Safety Procedures Manual (SPM). It is recommended that the SPM and IAGSA's Safety Management Systems Guideline (available at www.iagsa.ca) be consulted for additional detail when completing the assessment. Members are reminded that IAGSA is available to answer any questions and to aid with completing the questionnaire.

Completing the Questionnaire: The questionnaire is intended to assess compliance. It is understood that for many recommendations a simple yes or no answer is not appropriate. In these cases, possible responses include: Always, Sometimes or Never.

Always – Indicates that you are fully compliant, and you are required to indicate in the *Explanation of Compliance* column where in your procedures or process this is addressed.

Sometimes – Indicates that your compliance is situational dependant. In this case, an explanation is required which will be reviewed by IAGSA and a Notice of Difference <u>may</u> be required.

Never – Indicates that you are not compliant with the Recommended Practice. In this case, a Notice of Difference is required to be file with IAGSA.

Yes – Indicates that you are fully compliant, and you are required to indicate in the *Explanation of Compliance* column where in your procedures or process this is addressed.

No – Indicates that you are not compliant with the Recommended Practice. In this case, a Notice of Difference is required to be file with IAGSA.

Filing a Notice of Difference: For items of non-compliance or if an item of partial compliance is deemed to require one, a Notice of Difference must be filed with IAGSA. The item shall be reported using the IAGSA standard Notice of Difference Form and be completed in its entirety including; the specific Recommended Practice being deviated from, an explanation as to why the deviation exists, a risk assessment identifying that the deviation attains an equivalent level of safety and be signed off by the company's Accountable Executive.



IAGSA Member Self-Assessment Questionnaire

Company Name: Bell Ge	ospace			
Location: Edinburgh UK			Audit completed	by:
Date of Audit: 11 March	2025		Scotty Morrison-	-Smith
Pre-audit questionnaire of	completed by: Andr	ew Noonan		
Activity data reported?	Yes			
All incidents reported?	Yes			
Key Personnel	<u>Name</u>	Emai	<u>I</u>	Telephone
President	Scott Hammond	shammond@bellgeo.co	m	+12815916900
Dir of Operations	Joel Puryear	jpuryear@bellgeo.com		+1 (979) 549-2805
Total # Employees:	40			·

Contents				
Section	Description	Page		
Safety Management System	IAGSA Recommended Safety Management System Elements	3		
Planning – All Operations	Planning activities required for all survey operations	7		
Operating Standards	IAGSA Recommended Practices for all types of operations	10		
Towed Geophysical Arrays	IAGSA Recommended Practices for design and operation of Towed Arrays	19		
Geophysical Survey Flight	IAGSA Recommended Practices for geophysical survey flight training.	23		
Training				
Overwater and Offshore	IAGSA Recommended Practices for Over Water and Offshore geophysical survey	24		
Operations	Operations			
Training Requirements	IAGSA Recommended Supplemental Aircrew Training	23		
Supplemental Training	IAGSA Recommended Additional Safety Training	30		
Requirements				
Flight Performance Monitoring	IAGSA Recommendation for Flight Operations Quality Assurance Monitoring	30		



Organization – Safety Management Systems			
Title	IAGSA Recommendation	Compliance	Explanation of Compliance
		Level	
			of a Safety Management System which includes,
	as a minimum, the basic components a	nd elements outlined	in this section.
Safety Policy	Do you have a Health and Safety		
Statement and	Policy Statement which outlines the		
Objectives	accountable manager's commitment		
	to, and responsibility for safety? (The		
	wording of the policy should reflect the company's philosophy on managing safety and	∐ No	
	should become the foundation on which the		
	company's SMS is built.)		
	Are specific Health and Safety	⊠ Yes	
	performance goals set and	⊠ Yes	
	measured? (examples may include X%	□ No	
	reduction in injuries, training completion targets, timeframes for follow up to reported		
	issues, etc.)		
	Are specific accountabilities defined		
	for those personnel who hold	⊠ Yes	
	positions of responsibility and/or	□ No	
	authority within the organisation that		
	have a direct effect on the safety of		
	the operation?		
	Does the SMS identify key personnel	⊠ Yes	
	responsible for the implementation,		
	maintenance and overall function of	□ No	
	the SMS?		



	Is emergency response planning including coordination with clients, emergency services and other organizations defined and documented?	
	Are all safety processes, policies and practices which define the SMS documented?	
	Does your SMS documentation identify which records must be retained and the period for which they shall be retained for?	
	Do you have a drug and alcohol policy including a program to implement that policy?	
Safety Risk Management	The process of risk management involv assess their associated risk levels, and	le systematic methods to identify hazards, to itigations.
	Does your SMS outline a Hazard Identification process for examining each aspect of the company's operations for the purpose of identifying anything (e.g. conditions,	



	situations, practices, behaviors, etc.) that has the potential to cause harm?	
	Does your SMS define a safety reporting process so that safety hazards / concerns can be identified, and appropriate actions can be taken?	
	Does your SMS define a process for assessing risk (actual and potential) of all reported hazards?	
Safety Assurance	Does you SMS outline a process for the measurement of safety performance including progress towards goals and objectives?	
	Does your SMS define a process for internal audits and inspections to provide assurance that the policies and procedures are being followed?	
	Does your SMS define a process for the investigation of safety hazards, incidents and accidents with the aim of identifying root causes?	
	Does your SMS define a process to identify and assess the safety impact of any changes that pose a risk to safety? (examples include introduction of a new aircraft type, a new maintenance procedure, changes to key personnel, etc.)	



	Does your SMS define a process for continual improvement?	Yes No	
	Does the process for continual improvement define who is responsible to assess the effectiveness of the system?	Yes No	
	Does the organization's top management, at planned intervals, review the SMS to ensure its continuing suitability, adequacy and effectiveness?	Yes No	
Safety Promotion	Does your SMS include a mechanism through which lessons learned from safety event investigations and other safety-related activities are made available to all affected staff and stakeholders?	Yes No	
	Does your SMS describe the minimum safety promotion applications acceptable to the company? (The complexity of the company's organisation and facility will determine what types of safety communications are required.)	Yes No	



	Planning	- All Operations	3		
Title	IAGSA Recommendation	Compliance Level	Explanation of Compliance		
Survey Planning	The following is a list of IAGSA Recommended Practices which all members should take into account when planning airborne survey operations regardless of type of survey or terrain.				
	Prior to commencing a survey, do you conduct a detailed IAGSA risk assessment which identifies the safe	⊠ Always			
	survey height?	Sometimes Never			
	Prior to conducting a survey do you	I NOVOI			
	Prior to conducting a survey do you establish a crew rotation schedule which considers factors such as remoteness of site, severity of climate, quality of accommodation, food and personal considerations?	⊠ Always			
		☐ Sometimes ☐ Never			
	De veu heve e minimum temperature				
	Do you have a minimum temperature limit for cold weather operations?	⊠ Always			
		Sometimes			
		│			
		∐ N/A			



Do you limit the use of aircraft heaters or air-conditioning in the interest of "clean" data?	☐ Always☐ Sometimes☑ Never	
Do you require the use of oxygen for all aircrew for survey flights or portions thereof conducted above 10,000 feet ASL?	✓ Always☐ Sometimes☐ Never	
Are aircrew members required to wear long trousers or a flight suit, closed shoes, have gloves available and clothing appropriate for the environmental conditions?	✓ Always☐ Sometimes☐ Never	
For fixed wing surveys, is a risk assessment conducted to determine whether or not helmets should be worn by the flight crew members?	☐ Always☐ Sometimes☐ Never☑ N/A	Due to our ac type (DC-3T) and after a risk assessment by ALCI and the Chf Pilot our crew do not wear helmets on any survey. NOD completed



	For helicopter surveys, are the flight crew members required to wear a flight helmet?	☐ Always☐ Sometimes☐ Never	NA
	Are flight crew members paid or given an incentive based upon hours or kilometers flown?	☐ Always☐ Sometimes☑ Never	
Emergency Response Planning	Do you develop project specific emergency response plans for each project?	✓ Always☐ Sometimes☐ Never	
	Does your company have an overall crisis management plan?	☐ Yes ⊠ No	
Flight Following	Do you operate a satellite tracking system on all aircraft?	✓ Always☐ Sometimes☐ Never	



	Is the position reporting frequency of the tracking system set to 2 minute intervals as a minimum?	⊠ Yes □ No	
Single Pilot Only Surveys	Do you conduct single Pilot Only Surveys (no equipment operator)?	☐ Always☐ Sometimes☑ Never	
	If so, does the Pilot have equipment operation duties in addition to those normally associated with flying the aircraft?	☐ Always☐ Sometimes☐ Never☑ N/A	
	Are additional risks associated with single pilot only operations detailed in the risk assessment?	☐ Always☐ Sometimes☐ Never☑ N/A	



Operating Standards				
Minimum safe survey speeds	Are minimum safe survey speeds for single engine aircraft calculated at 130% of clean stall speed (Vs)?	☐ Always ☐ Sometimes ☐ Never	NA	
	Are minimum safe survey speeds for Multi-engine aircraft: 110% of best single engine rate of climb speed (Vyse), or minimum safe single engine speed (Vsse, if published)?	☑ Always☐ Sometimes☐ Never☐ N/A		
Minimum Fuel Standard	Is fuel planning for survey flights based upon 110% of planned consumption?	✓ Always☐ Sometimes☐ Never		
	Is minimum reserve fuel calculated as 30 minutes for fixed wing and 20 minutes for helicopter at normal cruise consumption rates?	✓ Always☐ Sometimes☐ Never		
	Do planned minimum fuel reserves consider site specific contingencies?	⊠ Always		



		Sometimes	
		☐ Never	
Flight and Duty Times	Are the following Flight & Duty Times adhered to?		
Single Pilot Operation	A maximum of 8 hours flight time per day.	☐ Always	NA
Maximum Flight Times		☐ Sometimes	
		☐ Never	
	A maximum of 5 hours flight time on survey per day (excluding transit time)	☐ Always	NA
		Sometimes	
		☐ Never	
	A maximum of 40 hours flight time in any 7 consecutive day period	☐ Always	NA
		Sometimes	
		☐ Never	
	A maximum of 100 hours flight time in any consecutive 28 day period.	☐ Always	NA
		Sometimes	
		☐ Never	



	A maximum of 1000 hours in any consecutive 365 day period.	☐ Always ☐ Sometimes ☐ Never	NA
	If extensions to the single pilot flight times are used has the extension criteria recommended by IAGSA been met?	☐ Always☐ Sometimes☐ Never☑ N/A	
Dual Pilot Operations Maximum Flight times	A maximum of 10 hours flight time per day.	✓ Always☐ Sometimes☐ Never	
	A maximum of 8 hours flight time on survey (excluding transit time).	☐ Always☐ Sometimes☐ Never	
	A maximum of 45 hours flight time in any consecutive 7 day period.	✓ Always☐ Sometimes☐ Never	



	A maximum of 120 hours flight time in any consecutive 28 day period.		
	A maximum of 1200 hours flight time in any consecutive 365 day period.	✓ Always☐ Sometimes☐ Never	
Maximum Duty Times	The maximum duty time in any one day shall not exceed 14 hours	✓ Always☐ Sometimes☐ Never	
	The pilot shall have a minimum of 2 days rest within a 14 day period. These may be taken separately or together. If taken separately, one day rest shall be defined as 30 consecutive hours free from duty.		
Emergency Beacon / Radio	Is each aircrew member required to carry on their person essential survival items including: a personal locator beacon means to start a fire, knife and a signal mirror?	☐ Always☑ Sometimes☐ Never	



Fuel Quality Control – Storage Tanks	The quality control of the fuel varies considerably at smaller centres. The crew must determine the adequacy of this quality control and take all available means to ensure against boarding contaminated fuel.				
Taliks	Is there a procedure in place to ensure that the following checks are required anytime a fuel source is unknown or questionable:				
a	Check that Fuel Quality Control Check and Delivery documents are current	⊠ Always			
	and available.	Sometimes			
		Never			
	Check that the fuel servicing vehicle / facility is identified with the fuel type	⊠ Always			
	handled.	Sometimes			
		Never			
	Check that the facility is clean and maintained.				
		Sometimes			
		☐ Never			
	Check that bonding wires and connections are in good condition.				
		Sometimes			
		☐ Never			



	Check that filter systems are in place and date of last element replacement.	✓ Always☐ Sometimes☐ Never	
	Check that a sample is clear and bright downstream of the filter.	✓ Always☐ Sometimes☐ Never	
	Request or conduct a water test with paste or syringe and capsules.	✓ Always☐ Sometimes☐ Never	
	Check that a sample from the low point of the tank is clear bright and free of water. If there is no low point water drain, do a dip of the tank using water paste.		
Fuel Quality Control - Drums	When using drummed fuel are there pro	ocedures in place to	ensure the following requirements?
	Verify the expiry date of the drums.	⊠ Always	
		☐ Sometimes	



		☐ Never
	A "go no-go" filter be used for all refueling from drums.	
		☐ Sometimes
		☐ Never
	All drum fuel is visually checked for clarity and color and water tested with	⊠ Always
	paste or fuel syringe and capsules before use.	Sometimes
		☐ Never
	Only clearly branded drums with both seals intact are be used unless the	
	pilot knows the "history" of the drum since the seals were broken and	Sometimes
	retests the fuel for contamination before use.	☐ Never
	Aircraft sump drains be checked before the first flight of the day and	
	after each refueling.	Sometimes
		☐ Never
	Drums are stored on their sides, clear of the ground with bungs horizontal in	



	an area not subject to flooding. Under- cover storage should be considered if drum stock are to be kept for a long time.	☐ Sometimes ☐ Never	
	When not in use, fuel pumps are protected from water and other contamination.	✓ Always☐ Sometimes☐ Never	
	Bungs should be sealed and the drum placed on its side for short term storage (i.e. overnight) of a partially filled drum.	☑ Always☐ Sometimes☐ Never	
Night Surveys	with a smooth air requirement, such as	for gravity surveys, it as there are adequa	VMC, but if the low height is removed coupled t may be desirable to conduct night flights. Such te procedures to prevent a "controlled flight into ts:
	Are night surveys flown at least 1000 feet above all obstacles within the operational area and a 10 nautical mile buffer around the operational area? Does the operational area	☐ Always ☐ Sometimes	



	include the maneuvering area for line turns and lead-ins?	Never N/A	
	Is a VMC reconnaissance flight performed in each block?	Always	
		Sometimes	
		Never	
		N/A	
Monitoring of radios	During survey flights, are radios and transponders turned on and selected to the appropriate ATC or flight service frequencies. Additionally, equipment permitting, common air to air and emergency frequencies (121.5MHz) should also be monitored.	Always Sometimes Never	
Turning Radius			rgin above the stall speed, however in a steep g and a stall in the turn at low level will likely
	Are all turns at low level limited to a maximum angle of bank of 30 degrees and be done at a constant altitude. Are climbs or descents allowed to be carried out during the turn?	Always Sometimes Never	



	Towed Geophysical Arrays						
Towed Geophysical Arrays – All	This section applies to all airborne surverotary or fixed wing aircraft.	eys utilizing geophys	ical arrays suspended below and/or towed by				
aircraft types	Do you operate towed geophysical arrays?	☐ Yes					
		⊠ No					
	Does the towed array have an STC/LSTC, engineering order or other						
	similar certificate or statement describing array specifications and flight test data?	☐ Yes					
		☐ No					
		⊠ N/A					
	Is there an Operating Manual for each array?	☐ Yes					
		☐ No					
		⊠ N/A					
	Does the Operating manual identify the maximum safe operating airspeed	☐ Yes					
	for the array?	☐ No					
		⊠ N/A					



Does the Operating Manual contain a parts list and maintenance manual containing the critical design specification for all parts and elements of the array?		Yes No	
•		N/A	
Does the Operations Manual contain a pre-flight checklist?		Yes	
		No	
		N/A	
Does the Operations Manual contain a schedule for routine preventative maintenance, recorded inspections		Yes	
and testing?		No	
	\boxtimes	N/A	
Is there a procedure in place to ensure that all required maintenance,		Yes	
inspections and testing are up to date prior to job start?		No	
	\boxtimes	N/A	
Is all maintenance performed by a qualified person endorsed by the		Yes	
manufacturer or operator?		No	



		⊠ N/A	
Towed Geophysical Arrays – Rotary Wing Aircraft	Has the cable weight and length been determined by an aeronautical engineer as to minimize the potential for cable recoil into main and tail rotors following the loss of load?	☐ Yes☐ No☑ N/A	
	Is there a weak link incorporated into the load bearing cable?	☐ Yes	
		⊠ N/A	
	Is the weak link located as close as possible to the attachment hook of the helicopter?	☐ Yes☐ No☑ N/A	
	Has the breaking strain of the weak link been specified by an aeronautical engineer?	☐ Yes☐ No☑ N/A	
	Is the maximum towed array airspeed and VNE (Velocity Never Exceed)	☐ Yes	



	placard placed on the aircraft instrument panel in the Pilot's view?	□ No □ N/A		
	Does the cargo hook arrangement allow the pilot to jettison the load without removing his/her hands from the flight controls? Do procedures include the requirement to test the helicopter cargo hook release mechanism?	☐ Yes ☐ No ☑ N/A		
Towed Geophysical Arrays – Fixed Wing	Is the aircraft fitted with a shearing mechanism which can cut the tow cable when the array needs to be jettisoned?	☐ Yes ☐ No ☑ N/A		
	Does the tow cable have a breaking strain which minimizes damage to the aircraft in the event the array snagged with ground objects?	☐ Yes ☐ No ☑ N/A		
Geophysical Survey Flight Training				



Training and Experience – All Operations	Does your training program contain a syllabus for low level geophysical flight training?		
	Does the Pilot training syllabus reflect the IAGSA training guidelines?		
	Are there documented criteria to assess Pilot competency?		
Simulator Training	In addition to the training in the actual aircraft, do pilots, where practical, undergo simulator training in a type specific simulator representing the aircraft being flown on survey? If so, at what frequency?	☐ Always☐ Sometimes☑ Never☐ N/A	
	Overwater ar	nd Offshore Surv	/eys
Minimum requirements for Over water and Off Shore Surveys	rotary wing aircraft.	o all overwater and o	off shore surveys flown in both fixed wing and
Training – Overwater & Offshore Surveys	Is Underwater Escape Training completed within the preceding three	☐ Always	BOSAT or Underwater Training is undertaken if the survey is offshore and out with the safe range our ac to return to land.



	years before undertaking the over water or offshore survey.		Sometimes Never	
	Are Ditching & Emergency Evacuation Procedures reviewed, crew members thoroughly briefed and simulated training to be conducted at the work site prior to the start of all over water or offshore work. This review should include a review of general emergency procedures that could potentially lead to a ditching and a discussion on the significance of sea state/wave height on ditching.		Always Sometimes Never	
Training - Off Shore Surveys	In addition to the above items, the following are to be included in offshore training:			
	Does Initial Training consist of a minimum of 10 hours training conducted by a pilot who has a minimum of 100 hours Offshore experience?		Yes No	
	Does Recurrent Training consist of a minimum of 5 hours training conducted annually by a pilot with the same qualifications as for the initial training: or prior to the start of an Offshore survey if pilot has completed	\boxtimes	Yes No	



	the initial training but has not flown Offshore for more than 90 days?			
	Alternatively, the above experience requirements may be waived if the Operator has in place a competency based training program which includes Offshore operations.			
Type of Aircraft – Over water / Offshore Operations	the exposure that would follow are low then the emphasis must be placed on choosing an aircraft that the probability of a ditching. Whereas, the aircraft criteria may be somewhat less stringent in less hars			
	For any survey that is over water or offshore in an area where rescue is not likely to occur within an anticipated acceptable exposure time and/or where anticipated sea states would make a successful ditching unlikely, is the use of a multi engine aircraft with performance characteristics such that in the event of an engine failure during an over water survey it can climb from survey height to 500 feet and return to shore or during an offshore survey it can climb from survey height and maintain prolonged flight on the remaining engine(s) to return to a suitable airport at the minimum IFR altitude utilized?	✓ Always☐ Sometime☐ Never	es	



	Are single engine piston aircraft used for over water/offshore surveys?	☐ Always	
		☐ Sometimes	
		Never	
Aircraft equipment – Offshore	Are aircraft equipped with at least the following gyroscopic instruments, each of which must be independent of the others: 2 x attitude indicator; 2 x heading indicator; 2 x turn and slip indicator or turn coordinator?		
	If a second pilot is to be part of the crew, is there a complete second set of basic flight instruments (attitude indicator, gyroscopic heading indicator, turn and slip or turn coordinator airspeed, altimeter, vertical speed) installed at the copilot's seating position?		
	Are there at least two (2) independent power sources to drive the gyroscopic instruments? - this may mean two vacuum pumps with all air driven gyroscopes or a mixture of air driven and electric gyroscopes		



provided loss of one power source leaves operational one set of three gyroscopic instruments (attitude, heading and turn rate indicators)		
Is there a radio or radar altimeter with a means of alerting the crew when height above the water falls below a minimum safety height selected by the crew? Is there a means of testing the alerting device prior to flight?		
Is there a minimum of one instantaneous vertical speed indicator (IVSI) to provide an instant alert of descent		
Do you require the use of weather radar where thunderstorms are present or could be expected?		
Are Rotary wing aircraft equipped with floatation aids such as "pop-outs floats"?	☐ Always☐ Sometimes☐ Never	NA



Emergency Equipment – Offshore Surveys	An upper torso restraint system, with a preference for a four point harness, for each crew member	⊠ Yes □ No	
	Are aircraft equipped with a 406 MHZ ELT?		
	Is the crew provided a covered life raft with a self erecting canopy that is equipped with a 406 MHZ ELT and normal emergency survival equipment? Does raft should include an inflatable floor for cold water operations?	⊠ Yes □ No	
	Are constant wear dual chamber life vests that contain an ELT aELT/EPIRB, flares and a signal mirror, worn by each crew member?	☐ Yes ☑ No	
	Are immersion/exposure suits worn if water and air temperatures warrant?	⊠ Yes □ No	
	Are all helmets and headsets fitted with double disconnect cords?	☐ Yes	



Weather – Offshore Surveys	Are Offshore survey flights conducted under VMC with minimums of 5 miles visibility and 1000 foot ceiling in the survey area?			
	Is a thorough weather briefing solicited (if available) and does it should include sea state/wave height and wind maximums in the survey area?			
	Supplemental Safe	ety Training Req	uirements	
Fire Extinguisher Training	Do all crew members on survey flights, including equipment operators, receive annual training in the use of fire extinguishers in fighting in flight fires?	⊠ Yes □ No		
Survey Crew Resource Management Training	Is Survey Crew Resource Management training provided to all crew members assigned to survey operations including: geophysicists; pilots; equipment operators; maintenance engineers; field technicians and field support staff at intervals not exceeding three years?	⊠ Yes □ No		
Flight Performance Monitoring				



Performance Monitoring	Are performance parameters, including aircraft speed, height above terrain and drape, periodically reviewed using data collected during surveys?	☐ Always☑ Sometimes☐ Never	
	Is the frequency of review such that any discrepancies on a particular survey or by a particular pilot can be identified as early as possible?	☐ Always☑ Sometimes☐ Never	