International Airborne Geophysics Safety Association

"SAFETY IN THE AIR BEGINS ON THE GROUND."

IAGSA Member Self-Assessment Questionnaire

Introduction: All IAGSA Active Members (survey companies) are required to complete and submit the Self-Assessment Questionnaire on an annual basis. IAGSA Associate Members such as air service providers, are not required to complete the questionnaire however, they may find it a useful reference as part of their internal audit process. The intent of this self-assessment process is to increase transparency of compliance levels within our membership through the publishing of completed assessments in the members-only area of our website, improve awareness of IAGSA Recommended Practices by requiring members to conduct an annual internal audit, and, in the case of non-conformances or variances, to drive our Notice of Difference process. This program does not replace the in-person audits conducted by IAGSA, but it does shift the focus to that of verification and surveillance.

Instructions: The questionnaire is derived from the Recommended Practices contained within the IAGSA Safety Procedures Manual (SPM). It is recommended that the SPM and IAGSA's Safety Management Systems Guideline (available at www.iagsa.ca) be consulted for additional detail when completing the assessment. Members are reminded that IAGSA is available to answer any questions and to aid with completing the questionnaire.

Completing the Questionnaire: The questionnaire is intended to assess compliance. It is understood that for many recommendations a simple yes or no answer is not appropriate. In these cases, possible responses include: Always, Sometimes or Never.

Always – Indicates that you are fully compliant, and you are required to indicate in the *Explanation of Compliance* column where in your procedures or process this is addressed.

Sometimes – Indicates that your compliance is situational dependant. In this case, an explanation is required which will be reviewed by IAGSA and a Notice of Difference may be required.

Never – Indicates that you are not compliant with the Recommended Practice. In this case, a Notice of Difference is required to be file with IAGSA.

Yes – Indicates that you are fully compliant, and you are required to indicate in the *Explanation of Compliance* column where in your procedures or process this is addressed.

No – Indicates that you are not compliant with the Recommended Practice. In this case, a Notice of Difference is required to be file with IAGSA.

Filing a Notice of Difference: For items of non-compliance or if an item of partial compliance is deemed to require one, a Notice of Difference must be filed with IAGSA. The item shall be reported using the IAGSA standard Notice of Difference Form and be completed in its entirety including; the specific Recommended Practice being deviated from, an explanation as to why the deviation exists, a risk assessment identifying that the deviation attains an equivalent level of safety and be signed off by the company's Accountable Executive.

IAGSA Member Self-Assessment Questionnaire

Company Name: SPECTREM AIR PTY LTD			
Location: LANSERIA AIRPORT, SOUTH AFRICA			**Audit completed by: Piet van Rensburg**
Date of Audit: 11 February 2026			
Pre-audit questionnaire completed by: Piet van Rensburg			
Activity data reported?	YES		
All incidents reported?	YES		
Key Personnel	**Name**	**Email**	**Telephone**
MANAGING DIRECTOR	LOUIS POLOME	louis@spectrem.co.za	**+27 82 453 8008**
OPERATIONS MANAGER	PIET VAN RENSBURG	piet@spectrem.co.za	**+27 79 516 8820**
CHIEF PILOT	MICHAEL BRINKCATE	mike@spectrem.co.za	**+27 83 389 3726**
Total # Employees:	18		

Contents

Section	Description	Page
Safety Management System	IAGSA Recommended Safety Management System Elements	3
Planning – All Operations	Planning activities required for all survey operations	7
Operating Standards	IAGSA Recommended Practices for all types of operations	10
Towed Geophysical Arrays	IAGSA Recommended Practices for design and operation of Towed Arrays	19
Geophysical Survey Flight Training	IAGSA Recommended Practices for geophysical survey flight training.	23
Overwater and Offshore Operations	IAGSA Recommended Practices for Over Water and Offshore geophysical survey Operations	24
Training Requirements	IAGSA Recommended Supplemental Aircrew Training	23
Supplemental Training Requirements	IAGSA Recommended Additional Safety Training	30
Flight Performance Monitoring	IAGSA Recommendation for Flight Operations Quality Assurance Monitoring	30

Organization – Safety Management Systems			
Title	**IAGSA Recommendation**	**Compliance Level**	**Explanation of Compliance**
Safety Policy Statement and Objectives	All IAGSA members shall work towards the implementation of a Safety Management System which includes, as a minimum, the basic components and elements outlined in this section.		
	Do you have a Health and Safety Policy Statement which outlines the accountable manager's commitment to, and responsibility for safety? *(The wording of the policy should reflect the company's philosophy on managing safety and should become the foundation on which the company's SMS is built.)*	☒ Yes ☐ No	Refer to Spectrem Safety Management Manual (SPECTREM_MAN_003) pg 9 for the statement
	Are specific Health and Safety performance goals set and measured? *(examples may include X% reduction in injuries, training completion targets, timeframes for follow up to reported issues, etc.)*	☒ Yes ☐ No	Refer to QA and Safety objectives document : (SPECTREM_SF_066) for yearly Quality and Safety objectives
	Are specific accountabilities defined for those personnel who hold positions of responsibility and/or authority within the organisation that have a direct effect on the safety of the operation?	☒ Yes ☐ No	Refer to Spectrem Safety Management Manual (SPECTREM_MAN_003) pg 14 – 16 for the duties of Accountable persons
	Does the SMS identify key personnel responsible for the implementation, maintenance and overall function of the SMS?	☒ Yes ☐ No	Refer to Spectrem Safety Management Structure Organigram (SPECTREM_SHE_052) for the key personnel

	Is emergency response planning including coordination with clients, emergency services and other organizations defined and documented?	☒ Yes ☐ No	Emergency response planning is covered in detail in the Spectrem Emergency Response Document (SPECTREM_SHE_017) as well as Spectrem Safety Management Manual (SPECTREM_MAN_003) pg 44 - 48
	Are all safety processes, policies and practices which define the SMS documented?	☒ Yes ☐ No	Refer Spectrem Safety Management Manual (SPECTREM_MAN_003)
	Does your SMS documentation identify which records must be retained and the period for which they shall be retained for?	☒ Yes ☐ No	Refer Spectrem Safety Management Manual (SPECTREM_MAN_003) pg 23 – 25 All documentation is controlled on the Auto Sheq Software.
	Do you have a drug and alcohol policy including a program to implement that policy?	☒ Yes ☐ No	Detailed policy document Intoxication Policy (SPECTREM_SHE_042)
Safety Risk Management	The process of risk management involves establishing simple systematic methods to identify hazards, to assess their associated risk levels, and to implement risk mitigations.		
	Does your SMS outline a Hazard Identification process for examining each aspect of the company's operations for the purpose of identifying anything (e.g. conditions,	☒ Yes ☐ No	Refer Spectrem Safety Management Manual (SPECTREM_MAN_003) Section 9

	situations, practices, behaviors, etc.) that has the potential to cause harm?		
	Does your SMS define a safety reporting process so that safety hazards / concerns can be identified, and appropriate actions can be taken?	☒ Yes ☐ No	Refer Spectrem Safety Management Manual (SPECTREM_MAN_003) Section 9
	Does your SMS define a process for assessing risk (actual and potential) of all reported hazards?	☒ Yes ☐ No	Refer Spectrem Safety Management Manual (SPECTREM_MAN_003) Section 9
Safety Assurance	Does you SMS outline a process for the measurement of safety performance including progress towards goals and objectives?	☒ Yes ☐ No	Refer Spectrem Safety Management Manual (SPECTREM_MAN_003) Section 12
	Does your SMS define a process for internal audits and inspections to provide assurance that the policies and procedures are being followed?	☒ Yes ☐ No	Refer Spectrem Safety Management Manual (SPECTREM_MAN_003) Section 13
	Does your SMS define a process for the investigation of safety hazards, incidents and accidents with the aim of identifying root causes?	☒ Yes ☐ No	Refer Spectrem Safety Management Manual (SPECTREM_MAN_003) Section 11
	Does your SMS define a process to identify and assess the safety impact of any changes that pose a risk to safety? *(examples include introduction of a new aircraft type, a new maintenance procedure, changes to key personnel, etc.)*	☒ Yes ☐ No	Refer Spectrem Safety Management Manual (SPECTREM_MAN_003) Section 14

	Does your SMS define a process for continual improvement?	☒ Yes ☐ No	Refer Spectrem Safety Management Manual (SPECTREM_MAN_003) Section 3
	Does the process for continual improvement define who is responsible to assess the effectiveness of the system?	☒ Yes ☐ No	L Polome is appointed Section 16.1 in terms of the RSA Occupational Health and Safety Act No 85.
	Does the organization's top management, at planned intervals, review the SMS to ensure its continuing suitability, adequacy and effectiveness?	☒ Yes ☐ No	1. The procedure and intervals for review are detailed in section 8.2 of the SMS manual. 2. Amendments are recorded in Section 20. 3. Full review of SMS manual done on 13 May 2021
Safety Promotion	Does your SMS include a mechanism through which lessons learned from safety event investigations and other safety-related activities are made available to all affected staff and stakeholders?	☒ Yes ☐ No	Refer Spectrem Safety Management Manual (SPECTREM_MAN_003) Section 12
	Does your SMS describe the minimum safety promotion applications acceptable to the company? *(The complexity of the company's organisation and facility will determine what types of safety communications are required.)*	☒ Yes ☐ No	Safety promotion applications are detailed in pg 16 – 18 of the Safety Management Manual (SPECTREM_MAN_003)

Planning – All Operations			
Title	**IAGSA Recommendation**	**Compliance Level**	**Explanation of Compliance**
Survey Planning	The following is a list of IAGSA Recommended Practices which all members should take into account when planning airborne survey operations regardless of type of survey or terrain.		
	Prior to commencing a survey, do you conduct a detailed IAGSA risk assessment which identifies the safe survey height?	☒ Always ☐ Sometimes ☐ Never	As detailed in SPECTREM_PRO_005 Logistical Planning Process.
	Prior to conducting a survey do you establish a crew rotation schedule which considers factors such as remoteness of site, severity of climate, quality of accommodation, food and personal considerations?	☒ Always ☐ Sometimes ☐ Never	As detailed in SPECTREM_PRO_005 Logistical Planning Process.
	Do you have a minimum temperature limit for cold weather operations?	☐ Always ☐ Sometimes ☐ Never ☒ N/A	As cold weather operations have not taken place for many years, no limit is set. However, should cold weather operations take place the IAGSA guideline of -35C will be used and noted in the applicable survey documents.

	Do you limit the use of aircraft heaters or air-conditioning in the interest of "clean" data?	☐ Always ☐ Sometimes ☒ Never	1. Aircraft not fitted with air-conditioning. 2. Heater system may be used during survey with no limit (Data not affected)
	Do you require the use of oxygen for all aircrew for survey flights or portions thereof conducted above 10,000 feet ASL?	☒ Always ☐ Sometimes ☐ Never	No surveys have been conducted at these altitudes.
	Are aircrew members required to wear long trousers or a flight suit, closed shoes, have gloves available and clothing appropriate for the environmental conditions?	☐ Always ☒ Sometimes ☐ Never	All areas compliant. Although generally worn there is no documented requirement to wear long trousers. In very hot conditions, this is not always possible as the aircraft is not air-conditioned.
	For fixed wing surveys, is a risk assessment conducted to determine whether or not helmets should be worn by the flight crew members?	☐ Always ☐ Sometimes ☐ Never ☒ N/A	IAGSA notification of Differences in force regarding use of Helmets in DC3T Risk assessment conducted.

	For helicopter surveys, are the flight crew members required to wear a flight helmet?	☒ Always ☐ Sometimes ☐ Never	Helicopter Standard Operating Procedure (SPECTREM_SOP_010)
	Are flight crew members paid or given an incentive based upon hours or kilometers flown?	☐ Always ☐ Sometimes ☒ Never	Spectrem Performance Incentive Scheme (SPECTREM_SF_024)
Emergency Response Planning	Do you develop project specific emergency response plans for each project?	☒ Always ☐ Sometimes ☐ Never	1. The Emergency response bridging document (SPECTREM_CHK_015) details specific ERP plans for each project. 2. SPECTREM_PRO_005 Logistical Planning Process
	Does your company have an overall crisis management plan?	☒ Yes ☐ No	Refer Spectrem Safety Management Manual (SPECTREM_MAN_003)
Flight Following	Do you operate a satellite tracking system on all aircraft?	☒ Always ☐ Sometimes ☐ Never	Spider tracks is used 1. The procedure is documented as SPECTREM_PRC_072 2. The Emergency response bridging document (SPECTREM_CHK_015)

	Is the position reporting frequency of the tracking system set to 2 minute intervals as a minimum?	☒ Yes ☐ No	As above
Single Pilot Only Surveys	Do you conduct single Pilot Only Surveys (no equipment operator)?	☐ Always ☐ Sometimes ☒ Never	N/A Single Pilot operations are not conducted
	If so, does the Pilot have equipment operation duties in addition to those normally associated with flying the aircraft?	☐ Always ☐ Sometimes ☐ Never ☒ N/A	N/A
	Are additional risks associated with single pilot only operations detailed in the risk assessment?	☐ Always ☐ Sometimes ☐ Never ☒ N/A	N/A

Operating Standards			
Minimum safe survey speeds	Are minimum safe survey speeds for single engine aircraft calculated at 130% of clean stall speed (Vs)?	☐ Always ☐ Sometimes ☐ Never	N/A Single engine aircraft not operated
	Are minimum safe survey speeds for Multi-engine aircraft: 110% of best single engine rate of climb speed (Vyse), or minimum safe single engine speed (Vsse, if published)?	☒ Always ☐ Sometimes ☐ Never ☐ N/A	Vyse = 96 kts. Therefore minimum survey speed is 105 kts. Normal/Nominal survey speed is 115 kts.
Minimum Fuel Standard	Is fuel planning for survey flights based upon 110% of planned consumption?	☒ Always ☐ Sometimes ☐ Never	Spectrem_MOP_001: STANDARD OPERATING PROCEDURES DC-3T SURVEY FLYING (Addendum to FlyJetStream MOP)
	Is minimum reserve fuel calculated as 30 minutes for fixed wing and 20 minutes for helicopter at normal cruise consumption rates?	☒ Always ☐ Sometimes ☐ Never	Spectrem_MOP_001: STANDARD OPERATING PROCEDURES DC-3T SURVEY FLYING (Addendum to FlyJetStream MOP)
	Do planned minimum fuel reserves consider site specific contingencies?	☒ Always ☐ Sometimes	Spectrem_MOP_001: STANDARD OPERATING PROCEDURES DC-3T SURVEY FLYING (Addendum to FlyJetStream MOP)

		☐ Never	
Flight and Duty Times	Are the following Flight & Duty Times adhered to?		
Single Pilot Operation Maximum Flight Times	A maximum of 8 hours flight time per day.	☐ Always ☐ Sometimes ☐ Never	N/A Single pilot surveys not conducted.
	A maximum of 5 hours flight time on survey per day (excluding transit time)	☐ Always ☐ Sometimes ☐ Never	N/A
	A maximum of 40 hours flight time in any 7 consecutive day period	☐ Always ☐ Sometimes ☐ Never	N/A
	A maximum of 100 hours flight time in any consecutive 28 day period.	☐ Always ☐ Sometimes ☐ Never	N/A

	A maximum of 1000 hours in any consecutive 365 day period.	☐ Always ☐ Sometimes ☐ Never	N/A
	If extensions to the single pilot flight times are used has the extension criteria recommended by IAGSA been met?	☐ Always ☐ Sometimes ☐ Never ☒ N/A	N/A
Dual Pilot Operations Maximum Flight times	A maximum of 10 hours flight time per day.	☒ Always ☐ Sometimes ☐ Never	Refer to FJS Flight operations manual for the FDP and hour limits. (Mostly more restrictive) Each pilot records their FDP as proof of compliance on a form which is submitted to the AOC and Spectrem Ops Manager monthly.
	A maximum of 8 hours flight time on survey (excluding transit time).	☒ Always ☐ Sometimes ☐ Never	As Above
	A maximum of 45 hours flight time in any consecutive 7 day period.	☒ Always ☐ Sometimes ☐ Never	As Above

	A maximum of 120 hours flight time in any consecutive 28 day period.	☒ Always ☐ Sometimes ☐ Never	As Above
	A maximum of 1200 hours flight time in any consecutive 365 day period.	☒ Always ☐ Sometimes ☐ Never	As Above
Maximum Duty Times	The maximum duty time in any one day shall not exceed 14 hours	☒ Always ☐ Sometimes ☐ Never	As Above
	The pilot shall have a minimum of 2 days rest within a 14 day period. These may be taken separately or together. If taken separately, one day rest shall be defined as 30 consecutive hours free from duty.	☒ Always ☐ Sometimes ☐ Never	As Above (3 days in 14 used as per SACAA regs – 1 in 7 and 2 consecutive in 14)
Emergency Beacon / Radio	Is each aircrew member required to carry on their person essential survival items including: a personal locator beacon means to start a fire, knife and a signal mirror?	☒ Always ☐ Sometimes ☐ Never	Moon-bag at each seat for each survey crew member containing PLB and listed survival equipment. IAGSA notification of Differences in force regarding the fact that it is not on each person at all time.

Fuel Quality Control – Storage Tanks	The quality control of the fuel varies considerably at smaller centres. The crew must determine the adequacy of this quality control and take all available means to ensure against boarding contaminated fuel. Is there a procedure in place to ensure that the following checks are required anytime a fuel source is unknown or questionable:		
	Check that Fuel Quality Control Check and Delivery documents are current and available.	☐ Always ☒ Sometimes ☐ Never	Due to size of our aircraft, we normally operate at bigger centres and make use of World Fuel Aviation for the supply of our fuel. In the case that we operate at smaller airports SPECTREM_CHK_040 will be used to check fuelling facility
	Check that the fuel servicing vehicle / facility is identified with the fuel type handled.	☐ Always ☒ Sometimes ☐ Never	As per above
	Check that the facility is clean and maintained.	☐ Always ☒ Sometimes ☐ Never	As per above
	Check that bonding wires and connections are in good condition.	☐ Always ☒ Sometimes ☐ Never	As per Above

	Check that filter systems are in place and date of last element replacement.	☐ Always ☒ Sometimes ☐ Never	As per above
	Check that a sample is clear and bright downstream of the filter.	☒ Always ☐ Sometimes ☐ Never	
	Request or conduct a water test with paste or syringe and capsules.	☐ Always ☒ Sometimes ☐ Never	Due to size of our aircraft, we normally operate at bigger centres and make use of World Fuel Aviation for the supply of our fuel. In the case that we operate at smaller airports SPECTREM_CHK_040 will be used to check fuelling facility
	Check that a sample from the low point of the tank is clear bright and free of water. If there is no low point water drain, do a dip of the tank using water paste.	☐ Always ☒ Sometimes ☐ Never	As per above
Fuel Quality Control - Drums	When using drummed fuel are there procedures in place to ensure the following requirements?		
	Verify the expiry date of the drums.	☐ Always ☐ Sometimes	N/A Due to the size of the aircraft we do not make use of fuel drums.

		☒ Never	
	A "go no-go" filter be used for all refueling from drums.	☐ Always ☐ Sometimes ☐ Never	N/A
	All drum fuel is visually checked for clarity and color and water tested with paste or fuel syringe and capsules before use.	☐ Always ☐ Sometimes ☐ Never	N/A
	Only clearly branded drums with both seals intact are be used unless the pilot knows the "history" of the drum since the seals were broken and retests the fuel for contamination before use.	☐ Always ☐ Sometimes ☐ Never	N/A
	Aircraft sump drains be checked before the first flight of the day and after each refueling.	☐ Always ☐ Sometimes ☐ Never	N/A
	Drums are stored on their sides, clear of the ground with bungs horizontal in	☐ Always	N/A

	an area not subject to flooding. Under-cover storage should be considered if drum stock are to be kept for a long time.	☐ Sometimes ☐ Never	
	When not in use, fuel pumps are protected from water and other contamination.	☐ Always ☐ Sometimes ☐ Never	N/A
	Bungs should be sealed and the drum placed on its side for short term storage (i.e. overnight) of a partially filled drum.	☐ Always ☐ Sometimes ☐ Never	N/A
Night Surveys	Typically, survey flights are conducted at low heights in day VMC, but if the low height is removed coupled with a smooth air requirement, such as for gravity surveys, it may be desirable to conduct night flights. Such flights can be conducted safely as long as there are adequate procedures to prevent a "controlled flight into terrain" CFIT accident. Are procedures in place to ensure the following requirements:		
	Are night surveys flown at least 1000 feet above all obstacles within the operational area and a 10 nautical mile buffer around the operational area? Does the operational area	☐ Always ☐ Sometimes	N/A Night surveys are not conducted.

	include the maneuvering area for line turns and lead-ins?	☐ Never ☒ N/A	
	Is a VMC reconnaissance flight performed in each block?	☐ Always ☐ Sometimes ☐ Never ☒ N/A	N/A Night surveys are not conducted.
Monitoring of radios	During survey flights, are radios and transponders turned on and selected to the appropriate ATC or flight service frequencies. Additionally, equipment permitting, common air to air and emergency frequencies (121.5MHz) should also be monitored.	☒ Always ☐ Sometimes ☐ Never	1. Dual radios monitored on applicable frequencies 2. 121.5 Mhz monitored when possible 3. Transponder and TCASII always on during survey
Turning Radius	During straight and level flight there may be a significant margin above the stall speed, however in a steep turn the stall speed may be reached quickly with little warning and a stall in the turn at low level will likely result in a fatal accident.		
	Are all turns at low level limited to a maximum angle of bank of 30 degrees and be done at a constant altitude. Are climbs or descents allowed to be carried out during the turn?	☒ Always ☐ Sometimes ☐ Never	Spectrem_MOP_001: STANDARD OPERATING PROCEDURES DC-3T SURVEY FLYING (Addendum to FlyJetStream MOP) – Rate 1 turns used.

Towed Geophysical Arrays			
Towed Geophysical Arrays – All aircraft types	This section applies to all airborne surveys utilizing geophysical arrays suspended below and/or towed by rotary or fixed wing aircraft.		
	Do you operate towed geophysical arrays?	☒ Yes ☐ No	
	Does the towed array have an STC/LSTC, engineering order or other similar certificate or statement describing array specifications and flight test data?	☐ Yes ☒ No ☐ N/A	The EM loop and axillary equipment has the necessary STC. Towed birds have engineering order and tested on regular basis.
	Is there an Operating Manual for each array?	☒ Yes ☐ No ☐ N/A	Form part of DC3 functionality Process SPECTREM_PRO_002
	Does the Operating manual identify the maximum safe operating airspeed for the array?	☒ Yes ☐ No ☐ N/A	Aircraft Flight Manual SUPPLEMENT No AAS-001 (Doc NO B0910000PG001)
	Does the Operating Manual contain a parts list and maintenance manual	☒ Yes	EM and MAG bird Tow Cable assembly procedure SPECTREM_PRC_005

	containing the critical design specification for all parts and elements of the array?	☐ No ☐ N/A	
	Does the Operations Manual contain a pre-flight checklist?	☒ Yes ☐ No ☐ N/A	DC3 inflight procedure: SPECTREM_PRC_016, Preflight Inside and outside Check List: SPECTREM_CHK_001 and Postflight inside and outside checklist: SPECTREM_CHK_016
	Does the Operations Manual contain a schedule for routine preventative maintenance, recorded inspections and testing?	☒ Yes ☐ No ☐ N/A	Refer to Operator Database for Preventative Maintenance Schedule
	Is there a procedure in place to ensure that all required maintenance, inspections and testing are up to date prior to job start?	☒ Yes ☐ No ☐ N/A	In Operator's Process flow SPECTREM_PRO_002, Functional checks before leaving Base: SPECTREM_TEC_017
	Is all maintenance performed by a qualified person endorsed by the manufacturer or operator?	☒ Yes ☐ No ☐ N/A	All systems operators are internally trained by the Electronic Manager
Towed Geophysical	Has the cable weight and length been determined by an aeronautical	☐ Yes	Currently no Helicopter operations

Arrays – Rotary Wing Aircraft	engineer as to minimize the potential for cable recoil into main and tail rotors following the loss of load?	☐ No ☒ N/A	
	Is there a weak link incorporated into the load bearing cable?	☐ Yes ☐ No ☒ N/A	N/A
	Is the weak link located as close as possible to the attachment hook of the helicopter?	☐ Yes ☐ No ☒ N/A	N/A
	Has the breaking strain of the weak link been specified by an aeronautical engineer?	☐ Yes ☐ No ☒ N/A	N/A
	Is the maximum towed array airspeed and VNE (Velocity Never Exceed) placard placed on the aircraft instrument panel in the Pilot's view?	☐ Yes ☒ No ☒ N/A	N/A

	Does the cargo hook arrangement allow the pilot to jettison the load without removing his/her hands from the flight controls? Do procedures include the requirement to test the helicopter cargo hook release mechanism?	☐ Yes ☐ No ☒ N/A	N/A
Towed Geophysical Arrays – Fixed Wing	Is the aircraft fitted with a shearing mechanism which can cut the tow cable when the array needs to be jettisoned?	☒ Yes ☐ No ☐ N/A	3 Options: Can be electrically engaged from the cockpit Can be electrically engaged by the system operator Can be manually cut by Operator/Pilot with a cable cutter
	Does the tow cable have a breaking strain which minimizes damage to the aircraft in the event the array snagged with ground objects?	☒ Yes ☐ No ☐ N/A	Yes and tested before any new installation.
Geophysical Survey Flight Training			
Training and Experience – All Operations	Does your training program contain a syllabus for low level geophysical flight training?	☒ Yes ☐ No	SPECTREM_TEC_074
	Does the Pilot training syllabus reflect the IAGSA training guidelines?	☒ Yes	SPECTREM_TEC_074

		☐ No	
	Are there documented criteria to assess Pilot competency?	☒ Yes ☐ No	SPECTREM_MOP_006
Simulator Training	In addition to the training in the actual aircraft, do pilots, where practical, undergo simulator training in a type specific simulator representing the aircraft being flown on survey? If so, at what frequency?	☐ Always ☐ Sometimes ☐ Never ☒ N/A	There is no DC3-T simulator available (worldwide) Refer Notification of Differences dated 21 Feb 2018.
Overwater and Offshore Surveys			
Minimum requirements for Over water and Off Shore Surveys	The following recommendations apply to all overwater and off shore surveys flown in both fixed wing and rotary wing aircraft.		
Training – Overwater & Offshore Surveys	Is Underwater Escape Training completed within the preceding three years before undertaking the over water or offshore survey.	☐ Always ☐ Sometimes ☐ Never	N/A No offshore surveys conducted.
	Are Ditching & Emergency Evacuation Procedures reviewed, crew members thoroughly briefed and simulated training to be conducted at the work		N/A No offshore surveys conducted.

	site prior to the start of all over water or offshore work. This review should include a review of general emergency procedures that could potentially lead to a ditching and a discussion on the significance of sea state/wave height on ditching.	☐ Always ☐ Sometimes ☐ Never	
Training - Off Shore Surveys	In addition to the above items, the following are to be included in offshore training:		
	Does Initial Training consist of a minimum of 10 hours training conducted by a pilot who has a minimum of 100 hours Offshore experience?	☐ Yes ☐ No	N/A No offshore surveys conducted.
	Does Recurrent Training consist of a minimum of 5 hours training conducted annually by a pilot with the same qualifications as for the initial training: or prior to the start of an Offshore survey if pilot has completed the initial training but has not flown Offshore for more than 90 days?	☐ Yes ☐ No	N/A No offshore surveys conducted.
	Alternatively, the above experience requirements may be waived if the Operator has in place a competency based training program which includes Offshore operations.		N/A No offshore surveys conducted.

Type of Aircraft – Over water / Offshore Operations	For an over water/offshore survey in an area with harsh conditions where the odds of surviving a ditching or the exposure that would follow are low then the emphasis must be placed on choosing an aircraft that reduces the probability of a ditching. Whereas, the aircraft criteria may be somewhat less stringent in less harsh conditions where the odds of a successful ditching and rescue are good.		
	For any survey that is over water or offshore in an area where rescue is not likely to occur within an anticipated acceptable exposure time and/or where anticipated sea states would make a successful ditching unlikely, is the use of a multi engine aircraft with performance characteristics such that in the event of an engine failure during an over water survey it can climb from survey height to 500 feet and return to shore or during an offshore survey it can climb from survey height and maintain prolonged flight on the remaining engine(s) to return to a suitable airport at the minimum IFR altitude utilized?	☒ Always ☐ Sometimes ☐ Never	N/A
	Are single engine piston aircraft used for over water/offshore surveys?	☐ Always ☐ Sometimes ☒ Never	N/A
	Are aircraft equipped with at least the following gyroscopic instruments,		N/A

Aircraft equipment – Offshore	each of which must be independent of the others: 2 x attitude indicator; 2 x heading indicator; 2 x turn and slip indicator or turn coordinator?	☒ Yes ☐ No	
	If a second pilot is to be part of the crew, is there a complete second set of basic flight instruments (attitude indicator, gyroscopic heading indicator, turn and slip or turn coordinator airspeed, altimeter, vertical speed) installed at the co-pilot's seating position?	☒ Yes ☐ No	N/A
	Are there at least two (2) independent power sources to drive the gyroscopic instruments? - this may mean two vacuum pumps with all air driven gyroscopes or a mixture of air driven and electric gyroscopes provided loss of one power source leaves operational one set of three gyroscopic instruments (attitude, heading and turn rate indicators)	☒ Yes ☐ No	N/A
	Is there a radio or radar altimeter with a means of alerting the crew when height above the water falls below a		2 x Radar Altimeter available with visual and audio warning

	minimum safety height selected by the crew? Is there a means of testing the alerting device prior to flight?	☒ Yes ☐ No	
	Is there a minimum of one instantaneous vertical speed indicator (IVSI) to provide an instant alert of descent	☒ Yes ☐ No	2 x IVSI available
	Do you require the use of weather radar where thunderstorms are present or could be expected?	☒ Always ☐ Sometimes ☐ Never	Weather radar installed on-board of the aircraft.
	Are Rotary wing aircraft equipped with floatation aids such as "pop-outs floats"?	☐ Always ☐ Sometimes ☐ Never	N/A
Emergency Equipment – Offshore Surveys	An upper torso restraint system, with a preference for a four point harness, for each crew member	☒ Yes ☐ No	N/A – No off-shore operations.
	Are aircraft equipped with a 406 MHZ ELT?	☒ Yes ☐ No	N/A

	Is the crew provided a covered life raft with a self erecting canopy that is equipped with a 406 MHZ ELT and normal emergency survival equipment? Does raft should include an inflatable floor for cold water operations?	☒ Yes ☐ No	N/A
	Are constant wear dual chamber life vests that contain an ELT aELT/EPIRB, flares and a signal mirror, worn by each crew member?	☐ Yes ☐ No	N/A
	Are immersion/exposure suits worn if water and air temperatures warrant?	☐ Yes ☐ No	N/A
	Are all helmets and headsets fitted with double disconnect cords?	☐ Yes ☐ No	N/A
Weather – Offshore Surveys	Are Offshore survey flights conducted under VMC with minimums of 5 miles visibility and 1000 foot ceiling in the survey area?	☐ Yes ☐ No	N/A – No off-shore operations.
	Is a thorough weather briefing solicited (if available) and does it should include sea state/wave height	☐ Yes	N/A

	and wind maximums in the survey area?	☐ No	
Supplemental Safety Training Requirements			
Fire Extinguisher Training	Do all crew members on survey flights, including equipment operators, receive annual training in the use of fire extinguishers in fighting in flight fires?	☒ Yes ☐ No	Fire Fighting training is done by all personnel every two years (as required by legislation)
Survey Crew Resource Management Training	Is Survey Crew Resource Management training provided to all crew members assigned to survey operations including: geophysicists; pilots; equipment operators; maintenance engineers; field technicians and field support staff at intervals not exceeding three years?	☐ Yes ☒ No	All Pilots perform CRM training annually See IAGSA temporary notification of differences filed.
Flight Performance Monitoring			
Performance Monitoring	Are performance parameters, including aircraft speed, height above terrain and drape, periodically reviewed using data collected during surveys?	☒ Always ☐ Sometimes ☐ Never	All parameters reported daily and graphically depicted using Geophysical software.
	Is the frequency of review such that any discrepancies on a particular survey or by a particular pilot can be identified as early as possible?	☒ Always ☐ Sometimes	Reported and reviewed daily as part of data QA conducted after each flight. Included and reviewed in weekly field safety meetings.

		☐ Never	